

View Online at <https://aerobasegroup.com/nsn/4820-01-261-2463>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

0.750 inches

Adjustable Pressure Range:

+10.0/+12.0 pounds per square inch

Maximum Operating Pressure:

1440.0 pounds per square inch single response

Outside Diameter:

3.875 inches 2nd end

Thickness:

0.562 inches 1st end

First Connection Face To Centerline Distance:

3.625 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

3.562 inches

Bolt Circle Diameter:

3.125 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

1.688 inches 2nd end

Special Features:

Inlet 0.750 in., outlet 1.000 in.

Material:

Steel body

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0