NSN 4820-01-261-7934

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-261-7934

····· -····· -···· -··················
Thread Direction:
Left-hand all ends
Flow Control Device:
Needle
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
300.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Valve Size:
0.500 inches
Adjustable Pressure Range:
+1.0/+300.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
First Connection Face To Centerline Distance:
1.062 inches
Second Connection Face To Centerline Distance:
2.500 inches
Material:
Copper alloy
Media For Which Designed:
Gas, natural 2nd response
Style Designator:
Err-090
Thread Series Designator:
Nptf 2nd end
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a

NSN 4820-01-261-7934

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

