

View Online at <https://aerobasegroup.com/nsn/4820-01-262-3130>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

500.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Valve Size:**

2.500 inches

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Outside Diameter:**

7.000 inches all ends

**Face To Face Distance:**

8.500 inches

**Thickness:**

0.688 inches all ends

**Bolt Hole Diameter:**

0.750 inches all ends

**Bolt Circle Diameter:**

5.500 inches all ends

**Flange Face Design:**

Raised straight all ends

**Raised Face Height:**

0.062 inches all ends

**Raised Face Diameter:**

4.125 inches all ends

**Special Features:**

This item has been reviewed for asbestos material. The current approved sources 30263 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984, stop check type

**Material:**

Copper alloy 922 seat or copper alloy 836 seat

**Material Specification:**

Astm b61 assn standard single material response seat or astm b62 assn standard single material response seat

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Furnished Items And Quantity:**

1 handwheel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0