

View Online at <https://aerobasegroup.com/nsn/4820-01-262-3132>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Union

**Maximum Operating Temp:**

550.0 degrees fahrenheit 1st response

**Connection Style:**

G9 plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

400.0 pounds per square inch 2nd response

**Thread Size:**

1.500 inches all ends

**Special Features:**

Stop-check type

**Material Specification:**

Astm b-62 assn standard single material response flow control device

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

Vthis item has been reviewed for asbestos material: the current approved sources; 82666 have indicated their part number contained asbestosto 1984, they continue to manufacture the same part number without asbestos materialafter 1984

**Thread Series Designator:**

Npt all ends

**Furnished Items And Quantity:**

1 handwheel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0