NSN 4820-01-263-0023

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-263-0023

Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+90.0/+110.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
6.000 inches 1st end
Thickness:
0.812 inches 2nd end
First Connection Face To Centerline Distance:
5.438 inches
Bolt Hole Diameter:
0.875 inches 2nd end
Second Connection Face To Centerline Distance:
5.438 inches
Bolt Circle Diameter:
4.500 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
3.625 inches 1st end
Material:
Steel comp 304 seat

NSN 4820-01-263-0023

Safety Relief Valve - Page 2 of 2



Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0