

View Online at <https://aerobasegroup.com/nsn/4820-01-264-8385>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

650.0 degrees fahrenheit 1st response 400.0 degrees fahrenheit 2nd response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

0.750 inches

Adjustable Pressure Range:

+156.0/+186.0 pounds per square inch

Maximum Operating Pressure:

125.0 pounds per square inch 1st response 200.0 pounds per square inch 2nd response

Outside Diameter:

4.250 inches 1st end 3.875 inches 2nd end

Thickness:

0.562 inches 1st end 0.688 inches 2nd end

First Connection Face To Centerline Distance:

3.312 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

3.250 inches

Bolt Circle Diameter:

3.125 inches 1st end 2.750 inches 2nd end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches 1st end 0.250 inches 2nd end

Raised Face Diameter:

2.000 inches 1st end 1.688 inches 2nd end

Material:

Steel body stainless steel flow control device stainless steel seat stainless steel stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0