## NSN 4820-01-264-8386

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-264-8386

Disk			
Bonnet Type:			
Inside spring			
Bonnet Attachment Method:			
Union			
Disk Loading Method:			
Spring			
Bolt Hole Quantity:			
4 all ends			
Maximum Operating Temp:			
600.0 degrees fahrenheit single response			
Valve Operation Method:			
Automatic			
Flange Shape:			
Round with holes all ends			
Connection Type:			
Flange all ends			
Valve Size:			
0.750 inches			
Adjustable Pressure Range:			
+156.0/+186.0 pounds per square inch			
Maximum Operating Pressure:			
600.0 pounds per square inch single response			
Outside Diameter:			
5.125 inches 2nd end			
Thickness:			
1.000 inches 2nd end			
First Connection Face To Centerline Distance:			
4.000 inches			
Bolt Hole Diameter:			
0.875 inches 2nd end			
Second Connection Face To Centerline Distance:			
3.750 inches			
Bolt Circle Diameter:			
3.500 inches all ends			
Flange Face Design:			
Raised straight all ends			
Raised Face Height:			
0.250 inches 2nd end			
Raised Face Diameter:			
2.000 inches 1st end			

## NSN 4820-01-264-8386

Safety Relief Valve - Page 2 of 2



ate	

Stainless steel stem

**Style Designator:** 

Err-090

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0