## NSN 4820-01-265-0357

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-265-0357

Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
8 all ends
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Vertical
Valve Size:
6.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
11.000 inches all ends
Face To Face Distance:
10.500 inches
Thickness:
1.000 inches all ends
Bolt Hole Diameter:
0.875 inches all ends
<b>Bolt Circle Diameter:</b>
9.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
8.500 inches all ends
Material:
Steel seat
Media For Which Designed:
Water-oil-gas 2nd response

## NSN 4820-01-265-0357

Stop-check Valve - Page 2 of 2



Styl	e D	esig	ınat	or

Straight through flanged ends

## **Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources 57574 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

## **Furnished Items And Quantity:**

1 handwheel

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A530b0