

View Online at <https://aerobasegroup.com/nsn/4820-01-265-0357>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Vertical

Valve Size:

6.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

11.000 inches all ends

Face To Face Distance:

10.500 inches

Thickness:

1.000 inches all ends

Bolt Hole Diameter:

0.875 inches all ends

Bolt Circle Diameter:

9.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

8.500 inches all ends

Material:

Steel seat

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight through flanged ends

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources 57574 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0