# NSN 4820-01-265-0357

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-265-0357

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

**Bonnet Attachment Method:** 

Bolted

**Disk Loading Method:** 

Spring

**Bolt Hole Quantity:** 

8 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

**Connection Type:** 

### Flange all ends

**Mounting Position:** 

Vertical

Valve Size:

6.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

**Outside Diameter:** 

11.000 inches all ends

Face To Face Distance:

10.500 inches

Thickness:

1.000 inches all ends

**Bolt Hole Diameter:** 

0.875 inches all ends

#### **Bolt Circle Diameter:**

9.500 inches all ends

#### Flange Face Design:

Raised straight all ends

#### **Raised Face Height:**

0.062 inches all ends

# **Raised Face Diameter:**

8.500 inches all ends

Material:

Steel seat

Media For Which Designed:

Water-oil-gas 2nd response

NSN 4820-01-265-0357

Stop-check Valve - Page 2 of 2



Style Designator:

Straight through flanged ends

## **Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources 57574 have indicated their part number contained

asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A530b0