NSN 4820-01-266-1320

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-266-1320

Flow Collifor Device.						
Disk						
Bonnet Type:						
Inside screw						
Bonnet Attachment Method:						
Bolted						
Bolt Hole Quantity:						
4 1st end						
Maximum Operating Temp:						
150.0 degrees fahrenheit single response						
Connection Style:						
Socket with brazing ring (tube) err-100						
Valve Operation Method:						
Automatic						
Flange Shape:						
Round with holes 1st end						
Connection Type:						
Unthreaded internal tube 2nd end						
Adjustable Pressure Range:						
+136.0/+150.0 pounds per square inch						
Maximum Operating Pressure:						
250.0 pounds per square inch single response						
Outside Diameter:						
4.875 inches 1st end						
Thickness:						
0.688 inches 1st end						
Bolt Hole Diameter:						
0.750 inches 1st end						
Bolt Circle Diameter:						
3.500 inches 1st end						
Flange Face Design:						
Plain all ends						
Outside Diameter Tube Accommodated:						
1.000 inches 2nd end						
Material:						
Nickel alloy flow control device						
Media For Which Designed:						
Gas, inert single response						
Style Designator:						
Err-090						
Shelf Life:						
N/a						

NSN 4820-01-266-1320

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0