NSN 4820-01-266-1322

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-266-1322

Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+26.0/+33.0 pounds per square inch
Outside Diameter:
5.000 inches 1st end
Thickness:
0.562 inches 2nd end
First Connection Face To Centerline Distance:
4.875 inches
Bolt Hole Diameter:
0.750 inches 2nd end
Second Connection Face To Centerline Distance:
5.125 inches
Bolt Circle Diameter:
6.000 inches 2nd end
Flange Face Design:
Plain all ends
Raised Face Height:
0.063 inches all ends
Raised Face Diameter:
5.000 inches 2nd end
Material:
Nickel alloy body
Style Designator:
Err-090

NSN 4820-01-266-1322

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0