

View Online at <https://aerobasegroup.com/nsn/4820-01-266-1323>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

750.0 degrees fahrenheit 1st response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

6.000 inches

Adjustable Pressure Range:

+68.0/+80.0 pounds per square inch

Maximum Operating Pressure:

95.0 pounds per square inch 1st response

Outside Diameter:

13.500 inches 1st end

Thickness:

1.125 inches 1st end

First Connection Face To Centerline Distance:

9.500 inches

Bolt Hole Diameter:

0.875 inches all ends

Second Connection Face To Centerline Distance:

9.437 inches

Bolt Circle Diameter:

9.500 inches 2nd end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

8.750 inches 2nd end

Material:

Stainless steel stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0