NSN 4820-01-266-1324

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-266-1324

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
650.0 degrees fahrenheit 1st response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+65.0/+84.0 pounds per square inch
Maximum Operating Pressure:
180.0 pounds per square inch 2nd response
Outside Diameter:
4.250 inches 1st end
Thickness:
0.562 inches 1st end
First Connection Face To Centerline Distance:
3.312 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.250 inches
Bolt Circle Diameter:
3.125 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 2nd end
Raised Face Diameter:
2.000 inches 1st end

NSN 4820-01-266-1324

Safety Relief Valve - Page 2 of 2



ate		

Stainless steel stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0