NSN 4820-01-267-0274

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-267-0274

Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
15.0 degrees fahrenheit single response
End Application:
Supply class aoe
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+160.0/+180.0 pounds per square inch
Maximum Operating Pressure:
225.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Outside Diameter:
3.875 inches all ends
Thickness:
0.344 inches all ends
First Connection Face To Centerline Distance:
3.000 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.000 inches
Bolt Circle Diameter:
2.750 inches all ends
Flange Face Design:
Plain all ends

NSN 4820-01-267-0274

Safety Relief Valve - Page 2 of 2



Material:
Stainless steel stem
Media For Which Designed:
Air single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0