## NSN 4820-01-267-5983

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-267-5983

Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Opening Pressure Setting:
12.0 pounds per square inch
Outside Diameter:
5.000 inches 2nd end
Thickness:
0.938 inches 1st end
First Connection Face To Centerline Distance:
4.875 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
5.125 inches
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches 2nd end
Raised Face Diameter:
5.000 inches 1st end
Material:
Stainless steel stem
Media For Which Designed:

Water-oil-gas single response

## NSN 4820-01-267-5983

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0