NSN 4820-01-270-2457

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-270-2457

Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
8 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Adjustable Pressure Range:
+2086.0/+2325.0 pounds per square inch
Outside Diameter:
8.500 inches 1st end
Thickness:
1.500 inches 1st end
First Connection Face To Centerline Distance:
6.188 inches
Bolt Hole Diameter:
1.125 inches 1st end
Second Connection Face To Centerline Distance:
6.062 inches
Bolt Circle Diameter:
6.625 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
5.000 inches 2nd end
Material:
Stainless steel stem
Media For Which Designed:
Air single response

NSN 4820-01-270-2457

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0