NSN 4820-01-270-5764

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-270-5764

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
750.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+68.0/+78.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Outside Diameter:
6.000 inches 2nd end
Thickness:
0.937 inches 2nd end
First Connection Face To Centerline Distance:
4.812 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
4.750 inches
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.312 inches 2nd end
Raised Face Diameter:
6.000 inches 1st end

NSN 4820-01-270-5764

Safety Relief Valve - Page 2 of 2



М	3	ŧ۵	ri	2	ŀ
IVI	a	re		a	٠.

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0