NSN 4820-01-270-5765

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-270-5765

Flow Control Device:				
Disk				
Bonnet Type:				
Inside spring				
Bonnet Attachment Method:				
Union				
Disk Loading Method:				
Spring				
Bolt Hole Quantity:				
8 all ends				
Maximum Operating Temp:				
400.0 degrees fahrenheit single response				
Valve Operation Method:				
Automatic				
Flange Shape:				
Round with holes all ends				
Connection Type:				
Flange all ends				
Valve Size:				
4.000 inches				
Adjustable Pressure Range:				
+59.0/+63.0 pounds per square inch				
Maximum Operating Pressure:				
200.0 pounds per square inch single response				
Outside Diameter:				
9.000 inches 2nd end				
Thickness:				
1.375 inches 2nd end				
First Connection Face To Centerline Distance:				
7.375 inches				
Bolt Hole Diameter:				
0.875 inches 1st end				
Second Connection Face To Centerline Distance:				
7.375 inches				
Bolt Circle Diameter:				
9.500 inches 1st end				
Flange Face Design:				
Raised straight all ends				
Raised Face Height:				
0.250 inches 2nd end				
Raised Face Diameter:				
8.500 inches 1st end				

NSN 4820-01-270-5765

Safety Relief Valve - Page 2 of 2



ate	

Stainless steel stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0