NSN 4820-01-270-6415

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-270-6415

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Sturgeon class ss (637)
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+10.0/+14.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
8.250 inches all ends
Thickness:
0.906 inches all ends
First Connection Face To Centerline Distance:
5.062 inches
Bolt Hole Diameter:
0.875 inches all ends
Second Connection Face To Centerline Distance:
5.062 inches
Bolt Circle Diameter:
6.625 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Media For Which Designed:
Gas, inert single response

NSN 4820-01-270-6415

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0