

View Online at <https://aerobasegroup.com/nsn/4820-01-271-6126>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Union

**Maximum Operating Temp:**

550.0 degrees fahrenheit 1st response

**Connection Style:**

G9 plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

300.0 pounds per square inch 1st response

**Thread Size:**

2.000 inches all ends

**Material:**

Plastic polytetrafluoroethylene packing

**Material Specification:**

Astm b-61 assn standard single material response body

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources, 82666 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Npt all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0