NSN 4820-01-272-4656

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-272-4656

| Flow Control Device: |
|--|
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 8 all ends |
| Maximum Operating Temp: |
| 450.0 degrees fahrenheit single response |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 4.000 inches |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 9.000 inches all ends |
| Face To Face Distance: |
| 11.500 inches |
| Thickness: |
| 0.922 inches all ends |
| Bolt Hole Diameter: |
| 0.625 inches all ends |
| Bolt Circle Diameter: |
| 7.500 inches all ends |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.062 inches all ends |
| Raised Face Diameter: |
| 6.188 inches all ends |
| Special Features: |
| Stop check type |
| Material: |
| Iron body |
| Style Designator: |

Err-090

NSN 4820-01-272-4656

Globe Valve - Page 2 of 2



| _ | | | | - | | |
|---|---|---|-----|---|------|--|
| C | h | 0 | Iŧ. | | ife: | |
| | | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0