NSN 4820-01-272-6665

Stop-check Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-272-6665

Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
450.0 degrees fahrenheit 1st response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
1.500 inches
Maximum Operating Pressure:
300.0 pounds per square inch 1st response
Outside Diameter:
5.000 inches all ends
Face To Face Distance:
6.000 inches
Thickness:
0.438 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
3.875 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Stop-check type
Material:
Copper alloy 922 or copper alloy 836
Material Specification:
Astm b61 assn standard single material response or astm b62 assn standard single material response
Media For Which Designed:
Steam single response

NSN 4820-01-272-6665

Stop-check Valve - Page 2 of 2



Style	Desig	nator:

Straight through flanged ends

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0