

View Online at <https://aerobasegroup.com/nsn/4820-01-273-1269>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

1000.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

1.500 inches

**Maximum Operating Pressure:**

285.0 pounds per square inch 2nd response

**Outside Diameter:**

5.000 inches all ends

**Face To Face Distance:**

6.500 inches

**Thickness:**

0.562 inches all ends

**Bolt Hole Diameter:**

0.625 inches all ends

**Bolt Circle Diameter:**

3.875 inches all ends

**Flange Face Design:**

Raised straight all ends

**Raised Face Height:**

0.062 inches all ends

**Raised Face Diameter:**

2.875 inches all ends

**Special Features:**

Loose disc; integral hard faced seat; conventional port; chrome trim

**Material:**

Steel uns k03504 body

**Material Specification:**

Astm a105 assn standard single material response body

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0