## NSN 4820-01-273-4716

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-273-4716

Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+30.0/+50.0 pounds per square inch
Outside Diameter:
3.875 inches 1st end
Thickness:
0.500 inches 1st end
First Connection Face To Centerline Distance:
2.750 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
2.750 inches
Bolt Circle Diameter:
2.750 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.688 inches 1st end
Material:
Steel body
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090

## NSN 4820-01-273-4716

Safety Relief Valve - Page 2 of 2



Furnished	Items A	and Quantity:
-----------	---------	---------------

1 lever

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0