

View Online at <https://aerobasegroup.com/nsn/4820-01-273-9100>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded or welded

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

500.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

5.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

10.000 inches all ends

Face To Face Distance:

14.000 inches

Thickness:

0.938 inches all ends

Bolt Hole Diameter:

0.875 inches all ends

Bolt Circle Diameter:

8.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

7.313 inches all ends

Material:

Steel uns j03002 body

Media For Which Designed:

Water, salt single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0