NSN 4820-01-274-4726

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-274-4726

Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Adjustable Pressure Range:
+10.0/+12.0 pounds per square inch
Maximum Operating Pressure:
275.0 pounds per square inch single response
Outside Diameter:
6.000 inches 1st end
Thickness:
0.625 inches 1st end
First Connection Face To Centerline Distance:
4.500 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
4.500 inches
Bolt Circle Diameter:
4.750 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
3.625 inches 1st end
Material:
Steel stem

NSN 4820-01-274-4726

Safety Relief Valve - Page 2 of 2



Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0