

View Online at <https://aerobasegroup.com/nsn/4820-01-275-4160>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Valve Size:

2.500 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

7.000 inches all ends

Face To Face Distance:

8.000 inches

Thickness:

0.562 inches all ends

Bolt Hole Diameter:

0.812 inches all ends

Bolt Circle Diameter:

6.000 inches all ends

Flange Face Design:

Plain all ends

Material Specification:

Qq-n-281 federal specification single material response stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight through flanged ends

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources, 30263 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0