

View Online at <https://aerobasegroup.com/nsn/4820-01-275-4163>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 1st end

Maximum Operating Temp:

165.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.500 inches

Adjustable Pressure Range:

+12.0/+25.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

6.500 inches 1st end

Thickness:

1.000 inches 1st end

First Connection Face To Centerline Distance:

4.375 inches

Bolt Hole Diameter:

0.875 inches 2nd end

Second Connection Face To Centerline Distance:

3.875 inches

Bolt Circle Diameter:

5.000 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches 2nd end

Raised Face Diameter:

3.625 inches 1st end

Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Media For Which Designed:

Water, salt single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0