

View Online at <https://aerobasegroup.com/nsn/4820-01-275-6152>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4 all ends

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Valve Size:**

3.000 inches

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Outside Diameter:**

7.500 inches all ends

**Thickness:**

0.625 inches all ends

**First Connection Face To Centerline Distance:**

4.625 inches

**Bolt Hole Diameter:**

0.750 inches all ends

**Second Connection Face To Centerline Distance:**

4.625 inches

**Bolt Circle Diameter:**

6.000 inches all ends

**Flange Face Design:**

Plain all ends

**Special Features:**

Stop-check type

**Material:**

Nickel alloy flow control device

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources; 30263 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Furnished Items And Quantity:**

1 handwheel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0