

View Online at <https://aerobasegroup.com/nsn/4820-01-277-6508>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

165.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.000 inches

Adjustable Pressure Range:

+30.0/+50.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Outside Diameter:

6.000 inches 1st end

Thickness:

0.500 inches 1st end

First Connection Face To Centerline Distance:

3.000 inches

Bolt Hole Diameter:

0.750 inches 1st end

Second Connection Face To Centerline Distance:

3.000 inches

Bolt Circle Diameter:

4.750 inches 1st end

Flange Face Design:

Plain all ends

Special Features:

Valve size 1 in. X 2 in.

Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Media For Which Designed:

Water, salt single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0