## NSN 4820-01-277-6508

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-277-6508

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
165.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Adjustable Pressure Range:
+30.0/+50.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
6.000 inches 1st end
Thickness:
0.500 inches 1st end
First Connection Face To Centerline Distance:
3.000 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
3.000 inches
Bolt Circle Diameter:
4.750 inches 1st end
Flange Face Design:
Plain all ends
Special Features:
Valve size 1 in. X 2 in.

## NSN 4820-01-277-6508

Safety Relief Valve - Page 2 of 2



Material:
Rubber butadiene-acrylonitrile class nbr flow control device
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A046b0