## NSN 4820-01-278-6173



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-278-6173 Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Union **Disk Loading Method:** Spring **Renewable Seat Ring Type: Bolted Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 450.0 degrees fahrenheit single response **Valve Operation Method:** Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 2.000 inches **Adjustable Pressure Range:** +90.0/+140.0 pounds per square inch **Maximum Operating Pressure:** 300.0 pounds per square inch single response **Outside Diameter:** 6.000 inches all ends Thickness: 0.500 inches all ends **First Connection Face To Centerline Distance:** 4.000 inches **Bolt Hole Diameter:** 0.750 inches all ends **Second Connection Face To Centerline Distance:** 2.625 inches **Bolt Circle Diameter:** 4.750 inches all ends Flange Face Design: Plain all ends

**Special Features:** Extended stem

## NSN 4820-01-278-6173

Safety Relief Valve - Page 2 of 2



Material:
Rubber butadiene-acrylonitrile class nbr flow control device
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A046b0