

View Online at <https://aerobasegroup.com/nsn/4820-01-278-6173>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Adjustable Pressure Range:

+90.0/+140.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Outside Diameter:

6.000 inches all ends

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

4.000 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

2.625 inches

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Plain all ends

Special Features:

Extended stem

Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0