## NSN 4820-01-280-3931

Globe Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-280-3931

Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
6.625 inches all ends
Face To Face Distance:
10.875 inches
Thickness:
0.938 inches all ends
Bolt Hole Diameter:
0.688 inches all ends
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Stop check type
Material:
Nickel alloy flow control device
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Supplementary Features:
This item has been reviewed for asbestos material; the current approved sources; 91643 have indicated their part number contained
asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

## NSN 4820-01-280-3931

Globe Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0