

View Online at <https://aerobasegroup.com/nsn/4820-01-281-0945>

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Union

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

406.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

2.500 inches

**Maximum Operating Pressure:**

225.0 pounds per square inch 2nd response

**Outside Diameter:**

7.000 inches all ends

**Face To Face Distance:**

6.750 inches

**Thickness:**

0.562 inches all ends

**Bolt Hole Diameter:**

0.750 inches all ends

**Bolt Circle Diameter:**

5.500 inches all ends

**Flange Face Design:**

Plain all ends

**Material Specification:**

Astm b-62 assn standard single material response body

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources, 82666 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0