NSN 4820-01-281-7370

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-281-7370

Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
End Application:
Wasp class Ihd
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Adjustable Pressure Range:
+30.0/+42.0 pounds per square inch
Outside Diameter:
6.000 inches 1st end
Thickness:
0.562 inches 1st end
First Connection Face To Centerline Distance:
4.500 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
4.125 inches
Bolt Circle Diameter:
4.750 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
3.625 inches 1st end
Material:
Stainless steel stem

NSN 4820-01-281-7370

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Specification Data:
81349-mil-v-20065d government specification
Specification Or Standard:
1 type and d composition
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0