NSN 4820-01-281-7371

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-281-7371

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 1st end8 2nd end

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Adjustable Pressure Range:

+69.0/+80.0 pounds per square inch

Outside Diameter:

7.500 inches 1st end6.500 inches 2nd end

Thickness:

0.938 inches 1st end0.875 inches 2nd end

First Connection Face To Centerline Distance:

4.938 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

4.750 inches

Bolt Circle Diameter:

6.000 inches 1st end5.000 inches 2nd end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

5.000 inches 1st end3.625 inches 2nd end

Material:

Steel bodystainless steel flow control devicestainless steel seatstainless steel stem

Style Designator:

Err-090



NSN 4820-01-281-7371

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

