NSN 4820-01-283-2991

Ball Valve - Page 1 of 2

Bonnet Attachment Method:

Maximum Operating Temp:

Bonnet Type: Inside screw

Threaded

4 all ends

Bolt Hole Quantity:



View Online at https://aerobasegroup.com/nsn/4820-01-283-2991

| 450.0 degrees fahrenheit single response |
|--|
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 2.000 inches |
| Maximum Operating Pressure: |
| 750.0 pounds per square inch single response |
| Outside Diameter: |
| 6.000 inches all ends |
| Face To Face Distance: |
| 7.000 inches |
| Thickness: |
| 0.625 inches all ends |
| Bolt Hole Diameter: |
| 0.750 inches all ends |
| Bolt Circle Diameter: |
| 4.750 inches all ends |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.062 inches all ends |
| Raised Face Diameter: |
| 3.625 inches all ends |
| Material: |
| Steel body |
| Media For Which Designed: |
| Water-oil-gas single response |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| |

NSN 4820-01-283-2991

Ball Valve - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A046b0