NSN 4820-01-283-7155

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-283-7155

Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+272.0/+300.0 pounds per square inch
Outside Diameter:
4.625 inches all ends
Thickness:
0.625 inches all ends
First Connection Face To Centerline Distance:
3.688 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
3.688 inches
Bolt Circle Diameter:
3.250 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches all ends
Raised Face Diameter:
1.688 inches all ends
Material:
Steel comp 304 seat
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-01-283-7155

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0