

View Online at <https://aerobasegroup.com/nsn/4820-01-283-9598>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

5.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

10.000 inches all ends

Thickness:

0.750 inches all ends

First Connection Face To Centerline Distance:

6.250 inches

Bolt Hole Diameter:

0.875 inches all ends

Second Connection Face To Centerline Distance:

5.750 inches

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy 400 stem

Material Specification:

Qq-n-281 federal specification single material response stem

Media For Which Designed:

Water, fresh single response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 30263 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0