NSN 4820-01-284-4242

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-284-4242

Pipe Size Accommodated:
1.250 inches 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Forrestal class cv
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+1401.0/+1800.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Criticality Code Justification:
Zzzy
Opening Pressure Setting:
1401.0 pounds per square inch
Material:
Nickel alloy 400 stem or nickel alloy r-405 stem
Material Specification:
Qq-n-281 federal specification single material response stem
Style Designator:
Err-090
Furnished Items And Quantity:
2 tailpiece and 1 plugged drain and 1 wrench
Reference Number Differentiating Characteristics:
Requires special cleaning and packaging iaw mil-c-52211, for oxygen/nitrogen/hydrogen service
Shelf Life:
N/a
Unit Of Measure:
<u></u>
Demilitarization:
No
Fiig:
A046b0