

View Online at <https://aerobasegroup.com/nsn/4820-01-284-4862>

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

450.0 degrees fahrenheit single response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Valve Size:**

2.500 inches

**Maximum Operating Pressure:**

300.0 pounds per square inch single response

**Outside Diameter:**

7.000 inches all ends

**Face To Face Distance:**

8.000 inches

**Thickness:**

0.562 inches all ends

**Bolt Hole Diameter:**

0.750 inches all ends

**Bolt Circle Diameter:**

5.500 inches all ends

**Flange Face Design:**

Plain all ends

**Special Features:**

Recommended for throttling usage

**Material:**

Copper alloy 922 flow control device or copper alloy 836 flow control device

**Media For Which Designed:**

Steam single response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources 30263 have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Furnished Items And Quantity:**

1 handwheel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0