NSN 4820-01-284-5439

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-284-5439

Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Adjustable Pressure Range:
+18.0/+26.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
122.0 pounds per square inch
Outside Diameter:
5.562 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
5.375 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
6.219 inches
Bolt Circle Diameter:
4.438 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device

NSN 4820-01-284-5439

Safety Relief Valve - Page 2 of 2



Qq-n-281 federal specification single material response seat or qq-n-288 federal specification single material response seat

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0