NSN 4820-01-284-6893

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-284-6893



Flow Control Device: Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

3.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Opening Pressure Setting:

21.0 pounds per square inch

Outside Diameter:

7.688 inches 1st end

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

5.062 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

5.062 inches

Bolt Circle Diameter:

6.562 inches 1st end

Flange Face Design:

Plain all ends

Material:

Stainless steel stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

NSN 4820-01-284-6893

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

