# NSN 4820-01-284-7410

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-284-7410



# Flow Control Device: Disk

Bonnet Type:

Inside screw

## **Bonnet Attachment Method:**

Bolted

#### **Bolt Hole Quantity:**

4 all ends

#### Maximum Operating Temp:

450.0 degrees fahrenheit single response

#### Valve Operation Method:

Automatic

Flange Shape:

#### Round with holes all ends

#### **Connection Type:**

Flange all ends

#### Valve Size:

3.000 inches

#### Adjustable Pressure Range:

+54.0/+65.0 pounds per square inch

# Maximum Operating Pressure:

210.0 pounds per square inch single response

#### **Outside Diameter:**

7.500 inches all ends

#### Thickness:

0.750 inches all ends

#### First Connection Face To Centerline Distance:

6.000 inches

#### Bolt Hole Diameter:

0.750 inches all ends

#### Second Connection Face To Centerline Distance:

6.000 inches

#### Bolt Circle Diameter:

6.000 inches all ends

#### Flange Face Design:

Raised straight all ends

#### **Raised Face Height:**

0.062 inches all ends

#### Raised Face Diameter:

5.000 inches all ends

### Material:

Steel body

# NSN 4820-01-284-7410

Safety Relief Valve - Page 2 of 2



#### Media For Which Designed:

Water-oil-gas single response

## Style Designator:

Err-090

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A046b0