NSN 4820-01-284-8159

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-284-8159

| Pipe Size Accommodated: |
|--|
| 4.000 inches all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Maximum Operating Temp: |
| 400.0 degrees fahrenheit single response |
| Connection Style: |
| Err-090 all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Butt weld pipe all ends |
| Maximum Operating Pressure: |
| 275.0 pounds per square inch single response |
| Special Features: |
| Stop check type |
| Material: |
| Steel uns j92800 bodysteel uns j92800 flow control deviceplastic polytetrafluoroethylene packingsteel comp 403 stem |
| Material Specification: |
| Astm a351 grade cf3m assn standard single material response bodyastm a351 grade cf3m assn standard single material response flow |
| control deviceastm a276 type 403 assn standard single material response stem |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| |
| |