## NSN 4820-01-285-7428

Check Valve - Page 1 of 2

**Thread Series Designator:** 

Unj all ends



View Online at https://aerobasegroup.com/nsn/4820-01-285-7428

view Online at https://aerobasegroup.com/his//+020-01-200-7-420
Thread Class:
3b 2nd end
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Minimum Operating Temp:
-70.0 degrees fahrenheit
Connection Style:
Gasket seal (boss) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 all ends
Maximum Operating Pressure:
600.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees 1st end
Special Features:
Fifth surface treatment: silicone, minus 480 degrees f to plus 480 degrees f for air, c02, 02, n2 applications
Material:
Aluminum alloy body
Material Specification:
Qq-a-200/3, alloy 2024, t4 federal specification 1st material response body and qq-a-225/8, alloy 6061, t651 federal specification 2nd
material response body
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:
Straight thru
Supplementary Features:
Appl to f-16d blk40/60

## NSN 4820-01-285-7428

Check Valve - Page 2 of 2



Shelf L	ife:
N/a	
Unit Of	Моз

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.