NSN 4820-01-285-8387

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-285-8387

Ball or disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Maximum Operating Pressure:
225.0 pounds per square inch single response
Opening Pressure Setting:
75.0 pounds per square inch
Outside Diameter:
7.000 inches all ends
Thickness:
0.562 inches all ends
First Connection Face To Centerline Distance:
4.750 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
4.750 inches
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy body
Style Designator:
Err-090
Shelf Life:
N/a

NSN 4820-01-285-8387

Safety Relief Valve - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A046b0