## NSN 4820-01-286-6616

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-286-6616

Pipe Size Accommodated:
1.000 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Union
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring 2nd end
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe 2nd end
Thready Qty Per Inch (tpi):
11-1/2 1st end
Maximum Operating Pressure:
Maximum Operating Pressure: 400.0 pounds per square inch single response
400.0 pounds per square inch single response
400.0 pounds per square inch single response  Thread Size:
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed:
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed:  Water-oil-gas single response
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed:  Water-oil-gas single response  Style Designator:
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed:  Water-oil-gas single response  Style Designator:  Err-090
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed:  Water-oil-gas single response  Style Designator:  Err-090  Thread Series Designator:
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material: Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed: Water-oil-gas single response  Style Designator: Err-090  Thread Series Designator: Nh 1st end
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material: Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed: Water-oil-gas single response  Style Designator: Err-090  Thread Series Designator: Nh 1st end  Shelf Life:
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed:  Water-oil-gas single response  Style Designator:  Err-090  Thread Series Designator:  Nh 1st end  Shelf Life:  N/a
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed:  Water-oil-gas single response  Style Designator:  Err-090  Thread Series Designator:  Nh 1st end  Shelf Life:  N/a
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material: Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed: Water-oil-gas single response  Style Designator: Err-090  Thread Series Designator: Nh 1st end  Shelf Life: N/a  Unit Of Measure:
400.0 pounds per square inch single response  Thread Size: 1.000 inches 1st end  Material:  Plastic polychlorotrifluoroethylene flow control device  Media For Which Designed:  Water-oil-gas single response  Style Designator:  Err-090  Thread Series Designator:  Nh 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: